

End mills




NR, 1 tooth cut over centre



CZ Frézy válcové čelní | NR, 1 břit přes střed

DE Schaftfräser | NR, 1 Schneide über die Mitte

RU Фрезы концевые с цилиндрическим хвостовиком | NR, с центрорежущим зубом



1245

1255



D k 12	d h 6	I1 1245	I1 1255	I2 1245	I2 1255	Z	124518	124518	125518	125518
6	6	57	68	13	24	4	.060	.060 TIALN	.060	.060 TIALN
7	10	66	80	16	30	4	.070	.070 TIALN	.070	.070 TIALN
8	10	69	88	19	38	4	.080	.080 TIALN	.080	.080 TIALN
9	10	69	88	19	38	4	.090	.090 TIALN	.090	.090 TIALN
10	10	72	95	22	45	4	.100	.100 TIALN	.100	.100 TIALN
11	12	79	102	22	45	4	.110	.110 TIALN	.110	.110 TIALN
12	12	83	110	26	53	4	.120	.120 TIALN	.120	.120 TIALN
13	12	83		26		4	.130	.130 TIALN		
14	12	83	110	26	53	4	.140	.140 TIALN	.140	.140 TIALN
15	12	83	110	26	53	4	.150	.150 TIALN	.150	.150 TIALN
16	16	92	123	32	63	4	.160	.160 TIALN	.160	.160 TIALN
17	16	92		32		4	.170	.170 TIALN		
18	16	92	123	32	63	4	.180	.180 TIALN	.180	.180 TIALN
19	16	92		32		4	.190	.190 TIALN		
20	20	104	141	38	75	4	.200	.200 TIALN	.200	.200 TIALN
21	20	104		38		4	.210	.210 TIALN		
22	20	104	141	38	75	5	.220	.220 TIALN	.220	.220 TIALN
24	25	121	166	45	90	5	.240	.240 TIALN	.240	.240 TIALN
25	25	121	166	45	90	5	.250	.250 TIALN	.250	.250 TIALN
26	25	121	166	45	90	5	.260	.260 TIALN	.260	.260 TIALN
28	25	121	166	45	90	5	.280	.280 TIALN	.280	.280 TIALN
30	25	121	166	45	90	5	.300	.300 TIALN	.300	.300 TIALN
32	32	133	186	53	106	6	.320	.320 TIALN	.320	.320 TIALN
36	32	133	186	53	106	6	.360	.360 TIALN	.360	.360 TIALN
40*	32	143	205	63	125	6	.40032	.40032 TIALN	.40032	.40032 TIALN

*) ≠ DIN 844

Cutting conditions | Řezné podmínky | Schnittbedingungen | Условия резания

		fz (mm/z)												
Material		Ap	Ae	Vc	Ø 6	Ø 8	Ø 10	Ø 12	Ø 16	Ø 18	Ø 20	Ø 25	Ø 30	Ø 40
P.1	≤ 600 N/mm²	1,5xD	0,5xD	45	0,02	0,025	0,035	0,04	0,07	0,08	0,09	0,1	0,115	0,14
P.2	≤ 850 N/mm²	1,5xD	0,5xD	39	0,02	0,025	0,035	0,04	0,07	0,08	0,09	0,1	0,115	0,14
P.4	≤ 900 N/mm²	1,5xD	0,5xD	30	0,02	0,025	0,035	0,04	0,07	0,08	0,09	0,1	0,115	0,14
M.2	750–850 N/mm²	1,5xD	0,5xD	15	0,02	0,025	0,035	0,04	0,07	0,08	0,09	0,1	0,115	0,14
K.1	≤ 820 N/mm²	1,5xD	0,5xD	35	0,02	0,025	0,035	0,04	0,07	0,08	0,09	0,1	0,115	0,14

TiAlN: Vc + 50 %